

## Technical data

Test Parameter		Situation		Effect
Optical Test	Visible Light transmission	ON	<b>WHITE</b> 80%±0.5%	High Transparency
		OFF	<4%	Excellent Protect privacy
	Haze	ON	4.2%	High transparency
		OFF	> 90%	Excellent protect privacy
	Visual Angle	ON	130°	Wide angle
	UV Blocking	ON	> 99%	Environmental protection material
		OFF	> 99%	
	Infrared Blocking	ON	> 20%	Environmental protection material
		OFF	> 80%	
	Solar Gain coefficient	ON	0.79	Environmental protection material
OFF		0.06		
Electrical Test	Power Supply	ON	65V±5v	Low voltage
	Response time	ON-- > OFF	60MS	fast reponse time
		OFF-- > ON	20MS	
Energy Consumption	ON	3.7w	Low consumptionSaving energy	
Size	Max size	Non adhesive Max width:1.8m,Adhesive max width:1.5m,Roll		
	Thickness	Thickness	0.36mm	Wide working temperature
Datas	Working temperature	ON/OFF	-20℃-70℃	
	Storage Temperature	ON/OFF	-30℃-60℃	
	Life time(Indoor)	ON/OFF	>100000hours	
Switch times	ON/OFF	>200000000	Long serivce life	